

**IN THE CLAIMS**

Claims 1, 3, 5, 11-13, 15, and 17-19 have been amended. Accordingly, the listing of claims 1-21 below will replace all prior versions of the claims in the application.

1. (currently amended) A process for olefin oligomerization in a reactor, the process comprising ~~the steps of:~~

(a) ~~providing a reaction mixture in the reactor, the reaction mixture comprising:~~

(i) ~~at least one reactant comprising at least one olefin monomer and optionally hydrogen and~~

(ii) ~~a catalyst system suitable for the oligomerization of olefin monomers;~~

(b) ~~contacting the olefin monomer and the catalyst system in a reaction zone;~~

(c) ~~monitoring the process by using Raman spectrometry equipment to provide an output signal representative of one or more chemical components of the reaction; and~~

(d) ~~recovering an oligomer.~~

2. (previously presented) The olefin oligomerization process of claim 1, wherein the output signal is representative of a concentration of one of the reactants or the oligomer.

3. (currently amended) The olefin oligomerization process of claim 1, comprising ~~the step of~~ adjusting the olefin oligomerization process in response to the output signal provided by the Raman spectrometry equipment.

4. (previously presented) The olefin oligomerization process of claim 1, wherein the olefin oligomerization process is adjusted by adjusting the amount within the reaction mixture of at least one of the reactants, the oligomer or the catalyst system.
5. (currently amended) The olefin oligomerization process of claim 1, wherein the Raman spectrometry equipment is operatively connected to a Raman fiber optic probe that is in contact with the reaction or the ~~polyolefin~~ olefin oligomer.
6. (previously presented) The olefin oligomerization process of claim 5, wherein the Raman fiber optic probe comprises fused silica fiber optic cables within a protective metal sheath.
7. (previously presented) The olefin oligomerization process of claim 5, wherein the Raman spectrometry equipment comprises low resolution Raman spectrometry equipment.
8. (previously presented) The olefin oligomerization process of claim 7, wherein the Raman low resolution spectrometry equipment has a resolution in the range of from about 15 wavenumbers to about 30 wavenumbers.
9. (previously presented) The olefin oligomerization process of claim 1, wherein the reactants comprise hydrogen.
10. (previously presented) The olefin oligomerization process of claim 1, wherein the process is a trimerization process.

11. (currently amended) The olefin oligomerization process of claim 1, wherein the monomer comprises is ethylene and the oligomer comprises is 1 – hexene.

12. (currently amended) The olefin oligomerization process of claim 1, wherein the process is performed in two or more reactors connected in series, wherein effluent from an upstream reactor is provided as input to a downstream reactor, wherein the monitoring ~~step~~ comprises determining a concentration of the monomer in the effluent by the Raman spectrometry equipment, and wherein the adjusting ~~step~~ comprises providing an amount of monomer or comonomer in addition to the effluent to the downstream reactor.

13. (currently amended) A method for monitoring and controlling an oligomerization process comprising:

contacting in a reaction zone under suitable conditions a reaction mixture comprising monomer and a catalyst system;

forming an oligomer;

making a first measurement of a concentration of the monomer using Raman

~~spectrometrie~~ spectrometry equipment; and

adjusting at least one oligomerization condition in response to the first measurement.

14. (previously presented) The method of claim 13, wherein the first measurement is obtained before or within the reaction zone.

15. (currently amended) The method of claim 14, ~~further comprising the steps of:~~  
making a second measurement of a concentration of the monomer using Raman  
~~spectrometric~~ spectrometry equipment;  
comparing the first measurement ~~concentration~~ with the second measurement  
~~concentration~~; and  
~~wherein the~~ adjusting the step at least one oligomerization condition in response to the  
comparing step the first measurement with the second measurement.
16. (previously presented) The method of claim 15, wherein the second measurement is  
obtained within or after the reaction zone.
17. (currently amended) The method of claim 13, wherein the first measurement is obtained  
from the reaction zone in both gas phase and liquid phase using the Raman ~~spectrometric~~  
spectrometry equipment.
18. (currently amended) The method of claim 13 ~~15~~, wherein the making a first measurement  
comprises:  
obtaining a Raman spectrum of the reaction mixture, and  
determining the first measurement through the use of a calibration model.
19. (currently amended) The method of claim 18 ~~13~~, ~~further comprising~~ ~~[[,]]~~ ~~prior to the~~  
~~contacting, the step of~~ developing the calibration model using partial least squares analysis.

20. (previously presented) The method of claim 19, wherein the Raman spectrometry equipment is low resolution Raman spectrometry equipment.
21. (previously presented) The method of claim 20, wherein the low resolution Raman spectrometry equipment has a resolution of about 15 wavenumbers to about 30 wavenumbers.
- 22-29. (canceled).